

ADLUS1A ASAVI1A ENBAT1A GOGOP1A KABMU1A  
MARNI1A MONLO1A PANTA1A PUMAM1A

TABULAR DESCRIPTION (1)

RNAV RWY36											
Serial	Path	Waypoint Identifier	Flyover	Course	Magnetic	Distance	Turn	Altitude	Speed	VPA/	Navigation
Number	Descriptor			° M (° T)	Variation	(NM)	Direction	(FT)	(KT)	TCH	Specification
010	IF	ADLUS	-	-	+0.75	-	-	+FL130 ; -FL180	-	-	RNAV1
020	TF	CM201	-	202°(200.70°)	+0.75	7.0	-	+FL130 ; -FL150	-	-	RNAV1
030	TF	CM202	-	202°(200.68°)	+0.75	14.3	L	@FL130	-250	-	RNAV1
040	TF	NAZAI (IAF)	-	181°(180.18°)	+0.75	17.2	R	7000	-	-	RNAV1
050	TF	MAKOK (IF)	-	271°(270.18°)	+0.75	7.2	-	5600	-210	-	RNAV1
010	IF	ASAVI	-	-	+0.75	-	-	+7000 ; -FL130	-	-	RNAV1
020	TF	CM401	-	307°(306.29°)	+0.75	7.8	L	-10000	-250	-	RNAV1
030	TF	CM402	-	274°(272.70°)	+0.75	9.8	-	+7000 ; -9000	-	-	RNAV1
040	TF	NAZAI (IAF)	-	274°(272.64°)	+0.75	7.3	L	7000	-	-	RNAV1
050	TF	MAKOK (IF)	-	271°(270.18°)	+0.75	7.2	-	5600	-210	-	RNAV1
010	IF	ENBAT	-	-	+0.75	-	-	+7000 ; -FL130	-250	-	RNAV1
020	TF	EASTA (IAF)	-	340°(338.74°)	+0.75	12.9	L	7000	-	-	RNAV1
030	TF	MAKOK (IF)	-	316°(315.18°)	+0.75	10.0	-	5600	-210	-	RNAV1
010	IF	GOGOP	-	-	+0.75	-	-	11000	-250	-	RNAV1
020	TF	CM601	-	009°(008.39°)	+0.75	8.7	R	+7000 ; -10000	-	-	RNAV1
030	TF	MAKOK (IF)	-	021°(019.87°)	+0.75	12.8	-	5600	-210	-	RNAV1
010	IF	KABMU	-	-	+0.75	-	-	+7000 ; -FL130	-	-	RNAV1
020	TF	CM401	-	274°(272.75°)	+0.75	9.0	-	-10000	-250	-	RNAV1
030	TF	CM402	-	274°(272.70°)	+0.75	9.8	-	+7000 ; -9000	-	-	RNAV1
040	TF	NAZAI (IAF)	-	274°(272.64°)	+0.75	7.3	L	7000	-	-	RNAV1
050	TF	MAKOK (IF)	-	271°(270.18°)	+0.75	7.2	-	5600	-210	-	RNAV1