

TABULAR DESCRIPTION (5)

RNAV RWY19L/19R											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/TCH	Navigation Specification
WILLA3C											
TRANSITION IGONI FROM L507											
010	IF	IGONI	-	-	+0.58	-	-	-	-	-	RNAV 1
020	TF	WILLA	-	105°(104.3°)	+0.58	9.1	-	-FL180	-280	-	RNAV 1
TRANSITION TARED FROM G463/P646											
010	IF	TARED	-	-	+0.58	-	-	-	-	-	RNAV 1
020	TF	WILLA	-	094°(093.7°)	+0.58	31.2	-	-FL180	-280	-	RNAV 1
TRANSITION IBETO FROM L524											
010	IF	IBETO	-	-	+0.58	-	-	-	-	-	RNAV 1
020	TF	WILLA	-	068°(067.4°)	+0.58	35.6	-	-FL180	-280	-	RNAV 1
TRANSITION PASTO FROM L301											
010	IF	PASTO	-	-	+0.58	-	-	-	-	-	RNAV 1
020	TF	WILLA	-	054°(053.4°)	+0.58	40.5	-	-FL180	-280	-	RNAV 1
TRANSITION BONVO FROM M502											
010	IF	BONVO	-	-	+0.58	-	-	-	-	-	RNAV 1
020	TF	WILLA	-	024°(023.0°)	+0.58	43.4	-	-FL180	-280	-	RNAV 1
010	IF	WILLA	-	-	+0.58	-	-	-FL180	-280	-	RNAV 1
020	TF	BAROK	-	105°(104.4°)	+0.58	7.9	-	-	-	-	RNAV 1
030	TF	BS510	-	105°(104.4°)	+0.58	8.9	-	-FL150 ; +FL140	-	-	RNAV 1
040	TF	INVEK	-	105°(104.4°)	+0.58	8.6	-	-	-250	-	RNAV 1
050	TF	BS508	-	105°(104.5°)	+0.58	11.6	R	+11000	-	-	RNAV 1
060	TF	BS506	-	195°(194.4°)	+0.58	11.0	-	-	-	-	RNAV 1
070	TF	BS504	-	195°(194.4°)	+0.58	4.9	L	+9000	-220	-	RNAV 1
080	TF	BS502	-	106°(105.0°)	+0.58	7.0	L	-	-	-	RNAV 1
090	TF	WALTZ	-	015°(014.5°)	+0.58	5.0	-	+6000	-	-	RNAV 1
100	VM	-	-	015°(-)	+0.58	-	-	-	-	-	RNAV 1