

INSTRUMENT AERODROME ELEV 590 FT
APPROACH HEIGHTS RELATED TO
CHART - ICAO THR RWY04 - ELEV 590 FT

BURI RAM / Buri ram (VTUO)

ILS or LOC z RWY04

TABULAR DESCRIPTION

ILS or LOC z RWY04											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/RDH	Navigation Specification
010	IF	RISBO	-	-	+0.77	-	-	@7000	-	-	RNP 1
020	TF	RAMEI (IAF)	-	082°(081.6°)	+0.77	10.0	L	@4000	-230	-	RNP 1
030	TF	UNTAB (IF)	-	073°(072.2°)	+0.77	8.5	-	@3000	-210	-	RNP 1
010	IF	VIREB	-	-	+0.77	-	-	+7000	-	-	RNP 1
020	TF	OTBET	-	263°(261.7°)	+0.77	8.0	L	+7000	-	-	RNP 1
030	TF	LAKOP (IAF)	-	249°(248.0°)	+0.77	14.5	R	+4000	-230	-	RNP 1
040	TF	UNTAB (IF)	-	306°(305.1°)	+0.77	7.0	-	@3000	-210	-	RNP 1
010	IF	UBMEM	-	-	+0.77	-	-	+7000	-	-	RNP 1
020	TF	UO103	-	184°(183.5°)	+0.77	17.4	R	+7000	-	-	RNP 1
030	TF	LAKOP (IAF)	-	216°(215.1°)	+0.77	16.9	R	+4000	-230	-	RNP 1
040	TF	UNTAB (IF)	-	306°(305.1°)	+0.77	7.0	-	@3000	-210	-	RNP 1
010	IF	UNTAB (IF)	-	-	+0.77	-	-	@3000	-210	-	RNP 1
TRANSITION TO ILS or LOC											
020	TF	UO101 (FAF)	-	036°(035.1°)	+0.77	5.8	-	@1900	-	-	ILS
030	TF	UO102 (MAPt)	Y	036°(035.1°)	+0.77	4.0	-	@640	-	-3.0/50	ILS
040	CA	-	-	036°(035.1°)	+0.77	-	-	+1100	-200	-	RNP 1
050	DF	UNTAB (IF)	-	-	+0.77	-	R	+3000	-200	-	RNP 1
060	HM	UNTAB (IF)	Y	036°(035.1°)	+0.77	1 minute	R	+3000	-210	-	RNP 1