

**TABULAR DESCRIPTION**

ILS or LOC z RWY02											
Serial	Path	Waypoint Identifier	Flyover	Course	Magnetic	Distance	Turn	Altitude	Speed	VPA/	Navigation
Number	Descriptor			° M (° T)	Variation	(NM)	Direction	(FT)	(KT)	RDH	Specification
010	IF	DUGEL (IAF)	-	-	+0.85	-	-	+7000	-	-	RNP 1
020	TF	ASUBI (IF)	-	007°(005.8°)	+0.85	6.0	-	+5000	-210	-	RNP 1
010	IF	OGENO (IAF)	-	-	+0.85	-	-	+7000	-	-	RNP 1
020	TF	ASUBI (IF)	-	081°(080.4°)	+0.85	8.2	-	+5000	-210	-	RNP 1
010	IF	MBOB (IAF)	-	-	+0.85	-	-	+7600	-	-	RNP 1
020	TF	EKVI	-	152°(151.0°)	+0.85	11.1	L	+7000	-	-	RNP 1
030	TF	ASUBI (IF)	-	112°(110.7°)	+0.85	10.0	-	+5000	-210	-	RNP 1
010	IF	INVAR (IAF)	-	-	+0.85	-	-	+7600	-	-	RNP 1
020	TF	EKVI	-	202°(200.6°)	+0.85	20.9	L	+7000	-	-	RNP 1
030	TF	ASUBI (IF)	-	112°(110.7°)	+0.85	10.0	-	+5000	-210	-	RNP 1
010	IF	ASUBI (IF)	-	-	+0.85	-	-	+5000	-210	-	RNP 1
TRANSITION TO ILS or LOC											
020	TF	CN001 (FAF)	-	022°(020.7°)	+0.85	5.0	-	@4000	-	-	ILS
030	TF	CN002 (SDF)	-	022°(020.7°)	+0.85	6.1	-	@1800	-	-	ILS
040	TF	CN003 (MAPt)	Y	022°(020.7°)	+0.85	2.9	-	@737	-	-3.4 / 58	ILS
050	CA	-	-	022°(020.7°)	+0.85	-	-	+1900	-	-	RNP 1
060	DF	ASUBI (IF)	-	-	+0.85	-	R	+5000	-210	-	RNP 1
070	HM	ASUBI (IF)	Y	022°(020.7°)	+0.85	1 minute	L	+5000	-230	-	RNP 1

**WAYPOINT LIST**

ILS or LOC z RWY02		
Waypoint Identifier	Coordinates	
INVAR	18° 58' 02.05" N	100° 39' 31.36" E
MBOB	18° 48' 08.12" N	100° 26' 03.27" E
EKVI	18° 38' 22.25" N	100° 31' 44.36" E
OGENO	18° 33' 27.22" N	100° 33' 07.59" E
DUGEL	18° 28' 53.32" N	100° 40' 57.94" E
ASUBI	18° 34' 49.75" N	100° 41' 36.01" E
CN001	18° 39' 31.54" N	100° 43' 27.52" E
CN002	18° 45' 14.84" N	100° 45' 43.49" E
CN003 (THR02)	18° 47' 58.24" N	100° 46' 48.31" E