

**TABULAR DESCRIPTION**

<b>ILS or LOC z RWY19R</b>											
<b>Serial Number</b>	<b>Path Descriptor</b>	<b>Waypoint Identifier</b>	<b>Flyover</b>	<b>Course ° M (° T)</b>	<b>Magnetic Variation</b>	<b>Distance (NM)</b>	<b>Turn Direction</b>	<b>Altitude (FT)</b>	<b>Speed (KT)</b>	<b>VPA/RDH</b>	<b>Navigation Specification</b>
010	IF	REWCO (IAF)	-	-	+0.58	-	-	+5000	-220	-	RNAV 1
020	TF	RYAUN (IF)	-	195°(194.4°)	+0.58	5.0	-	+3500	-	-	RNAV 1
<b>TRANSITION TO ILS or LOC</b>											
030	TF	ROMME	-	195°(194.4°)	+0.58	4.6	-	+2500	-	-	ILS
040	TF	BS588 (FAP/FAF)	-	195°(194.4°)	+0.58	3.9	-	@2000	-	-	ILS
050	TF	MAPt (LOC only) @ RW19R	Y	195°(194.4°)	+0.58	6.1	-	@54	-	-3.0/50	ILS
060	CA	-	-	195°(194.4°)	+0.58	-	-	+1000	-190	-	RNAV 1
070	DF	RIPSO	-	-	+0.58	-	R	-	-190	-	RNAV 1
080	HM	RIPSO	Y	035°(034.3°)	+0.58	1 minute	L	+3000	-230	-	RNAV 1

**WAYPOINT LIST**

<b>ILS or LOC z RWY19R</b>		
<b>Waypoint Identifier</b>	<b>Coordinates</b>	<b>Pronunciation</b>
REWCO	14° 01' 21.29" N 100° 49' 37.68" E	REW - COH
RYAUN	13° 56' 26.99" N 100° 48' 20.12" E	RAI - AAN
ROMME	13° 51' 56.84" N 100° 47' 08.98" E	ROM - MEE
BS588	13° 48' 09.23" N 100° 46' 09.07" E	-
RW19R	13° 42' 13.21" N 100° 44' 35.44" E	-
RIPSO	13° 33' 44.05" N 100° 39' 50.12" E	RIP - SO

CHANGE: AD ELEV. THR ELEV.