

TABULAR DESCRIPTION (6)

RNAV RWY20R											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
SEMBO1E TO A464											
010	-	DER RWY20R	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	195°(194.4°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS940	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS932	-	285°(284.3°)	+ 0.6	7.5	-	-	-	-	RNAV 1
050	TF	GUGOT	-	002°(001.5°)	+ 0.6	6.4	-	-10000	-	-	RNAV 1
060	TF	BS936	-	002°(001.5°)	+ 0.6	6.9	-	-	-	-	RNAV 1
070	TF	KABUT	-	329°(328.4°)	+ 0.6	11.5	-	+FL140	-	-	RNAV 1
080	TF	BS938	-	343°(342.8°)	+ 0.6	18.5	-	+FL180	-	-	RNAV 1
090	TF	ANRIP	-	343°(342.8°)	+ 0.6	14.1	-	-	-	-	RNAV 1
100	TF	TANGO	-	343°(342.8°)	+ 0.6	13.1	-	-	-	-	RNAV 1
110	TF	SEMBO	-	006°(005.1°)	+ 0.6	13.6	-	-	-	-	RNAV 1
TANGO1E TO Y6											
010	-	DER RWY20R	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	195°(194.4°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS940	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS932	-	285°(284.3°)	+ 0.6	7.5	-	-	-	-	RNAV 1
050	TF	GUGOT	-	002°(001.5°)	+ 0.6	6.4	-	-10000	-	-	RNAV 1
060	TF	BS936	-	002°(001.5°)	+ 0.6	6.9	-	-	-	-	RNAV 1
070	TF	KABUT	-	329°(328.4°)	+ 0.6	11.5	-	+FL140	-	-	RNAV 1
080	TF	BS938	-	343°(342.8°)	+ 0.6	18.5	-	+FL180	-	-	RNAV 1
090	TF	ANRIP	-	343°(342.8°)	+ 0.6	14.1	-	-	-	-	RNAV 1
100	TF	TANGO	-	343°(342.8°)	+ 0.6	13.1	-	-	-	-	RNAV 1