

TABULAR DESCRIPTION (8)

RNAV RWY20R											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
UKERA1E TO G458											
010	-	DER RWY20R	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	195°(194.4°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS940	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS928	-	230°(229.1°)	+ 0.6	11.6	-	-10000	-	-	RNAV 1
050	TF	BS929	-	222°(221.3°)	+ 0.6	14.8	-	-FL160	-	-	RNAV 1
060	TF	BS930	-	222°(221.3°)	+ 0.6	12.1	-	-FL180	-	-	RNAV 1
070	TF	SABIS	-	222°(221.2°)	+ 0.6	4.7	-	-	-	-	RNAV 1
080	TF	UKERA	-	191°(189.9°)	+ 0.6	58.5	-	-	-	-	RNAV 1
VANKO1E TO Y8											
010	-	DER RWY20R	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	195°(194.4°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS940	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS928	-	230°(229.1°)	+ 0.6	11.6	-	-10000	-	-	RNAV 1
050	TF	BS929	-	222°(221.3°)	+ 0.6	14.8	-	-FL160	-	-	RNAV 1
060	TF	BS930	-	222°(221.3°)	+ 0.6	12.1	-	-FL180	-	-	RNAV 1
070	TF	SABIS	-	222°(221.2°)	+ 0.6	4.7	-	-	-	-	RNAV 1
080	TF	VANKO	-	226°(225.6°)	+ 0.6	35.3	-	-	-	-	RNAV 1