

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

BANGKOK/Suvarnabhumi Intl (VTBS)

RNAV RWY02L

ALBOS1F BONVO1F BUT1F DOSBU1F
GOMES1F HHN1F KASNI1F LIPLI1F
NOBER1F NUNLI1F PASTO1F REGOS1F
RYN1F SELKA1F SEMBO1F TANGO1F
TARED1F TL1F UKERA1F VANKO1F

TABULAR DESCRIPTION (6)

RNAV RWY02L

Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
RYN1F TO N891											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	R	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	ASANI	-	091°(090.4°)	+ 0.6	11.3	-	-8000	-	-	RNAV 1
060	TF	BS126	-	124°(123.1°)	+ 0.6	18.3	-	-	-	-	RNAV 1
070	TF	GOMES	-	130°(129.4°)	+ 0.6	26.3	-	-	-	-	RNAV 1
080	TF	RYN	-	172°(171.6°)	+ 0.6	37.5	-	-	-	-	RNAV 1
SELKA1F TO A1, Y14											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	R	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	ASANI	-	091°(090.4°)	+ 0.6	11.3	-	-8000	-	-	RNAV 1
060	TF	SELKA	-	062°(061.1°)	+ 0.6	60.7	-	-	-	-	RNAV 1
SEMBO1F TO A464											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	R	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	BS131	-	015°(014.4°)	+ 0.6	6.7	-	-	-	-	RNAV 1
060	TF	BS135	-	015°(014.4°)	+ 0.6	5.3	-	-	-	-	RNAV 1
070	TF	BS136	-	015°(014.5°)	+ 0.6	16.6	-	-	-	-	RNAV 1
080	TF	BS137	-	285°(284.6°)	+ 0.6	15.2	-	-FL150; +FL140	-	-	RNAV 1
090	TF	ANRIP	-	285°(284.5°)	+ 0.6	20.6	-	-	-	-	RNAV 1
100	TF	TANGO	-	343°(342.8°)	+ 0.6	13.1	-	-	-	-	RNAV 1
110	TF	SEMBO	-	006°(005.1°)	+ 0.6	13.6	-	-	-	-	RNAV 1