

**STANDARD DEPARTURE CHART-
INSTRUMENT (SID) - ICAO**

**BANGKOK/Don Mueang Intl (VTBD)
RNAV RWY21L**

ALBOS3C BONVO3C NOBER4C
NUNLI3C OLVUK3C PASTO3C
RIVDU3C ROBKA3C SEMBO4C
TARED3C UPKUP3C

TABULAR DESCRIPTION (1)

RNAV RWY21L											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
ALBOS3C TO R474											
010	-	DER RWR21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	BD207	-	354°(353.5°)	+ 0.6	10.8	-	+10000	-	-	RNAV 1
050	TF	DISCO	-	354°(353.5°)	+ 0.6	19.2	-	-FL130	-	-	RNAV 1
060	TF	BD208	-	053°(052.1°)	+ 0.6	7.0	-	-	-	-	RNAV 1
070	TF	BD209	-	073°(072.6°)	+ 0.6	21.2	-	-FL150 ; +FL140	-	-	RNAV 1
080	TF	ALBOS	-	073°(072.6°)	+ 0.6	19.1	-	-	-	-	RNAV 1
BONVO3C TO M502											
010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	OBMAR	-	273°(272.2°)	+ 0.6	15.4	-	-	-	-	RNAV 1
050	TF	BONVO	-	230°(229.8°)	+ 0.6	22.7	-	-	-	-	RNAV 1
NOBER4C TO B346/W39, W21											
010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	BD207	-	354°(353.5°)	+ 0.6	10.8	-	+10000	-	-	RNAV 1
050	TF	DISCO	-	354°(353.5°)	+ 0.6	19.2	-	-FL130	-	-	RNAV 1
060	TF	RMDU	-	016°(015.3°)	+ 0.6	14.8	-	-	-	-	RNAV 1
070	TF	NOBER	-	030°(029.5°)	+ 0.6	38.9	-	-	-	-	RNAV 1
NUNLI3C TO L507											
010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	BD207	-	354°(353.5°)	+ 0.6	10.8	-	+10000	-	-	RNAV 1
050	TF	DISCO	-	354°(353.5°)	+ 0.6	19.2	-	-FL130	-	-	RNAV 1
060	TF	NUNLI	-	295°(294.2°)	+ 0.6	56.5	-	-	-	-	RNAV 1

CHANGE : CHART TITLE. REVISED TABULAR DESCRIPTION.