

**STANDARD DEPARTURE CHART-  
INSTRUMENT (SID) - ICAO**

**BANGKOK/Don Mueang Intl (VTBD)  
RNAV RWY21L**

ALBOS3C BONVO3C NOBER4C  
NUNLI3C OLVUK3C PASTO3C  
RIVDU3C ROBKA3C SEMBO4C  
TARED3C UPKUP3C

**TABULAR DESCRIPTION (3)**

**RNAV RWY21L**

Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
SEMBO4C TO A464											
010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	BD207	-	354°(353.5°)	+ 0.6	10.8	-	+10000	-	-	RNAV 1
050	TF	DISCO	-	354°(353.5°)	+ 0.6	19.2	-	-FL130	-	-	RNAV 1
060	TF	RMDU	-	016°(015.3°)	+ 0.6	14.8	-	-	-	-	RNAV 1
070	TF	SEMBO	-	340°(338.9°)	+ 0.6	12.2	-	-	-	-	RNAV 1

**TARED3C TO G463/P646**

010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	INTOS	-	-	+ 0.6	-	R	-8000	-	-	RNAV 1
040	TF	TEMPO	-	299°(297.9°)	+ 0.6	27.0	-	-	-	-	RNAV 1
050	TF	TARED	-	304°(303.6°)	+ 0.6	27.6	-	-	-	-	RNAV 1

**UPKUP3C TO Y16**

010	-	DER RWY21L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	CA	-	-	209°(208.7°)	+ 0.6	-	-	+1500	-200	-	RNAV 1
030	DF	BD201	-	-	+ 0.6	-	R	-	-	-	RNAV 1
040	TF	BD202	-	227°(226.6°)	+ 0.6	5.2	-	-8000 ; +5000	-	-	RNAV 1
050	TF	BD203	-	175°(174.7°)	+ 0.6	8.6	-	-	-	-	RNAV 1
060	TF	MATLO	-	101°(100.3°)	+ 0.6	8.5	-	+11000	-	-	RNAV 1
070	TF	BD204	-	082°(081.5°)	+ 0.6	23.1	-	-	-	-	RNAV 1
080	TF	BD205	-	052°(051.4°)	+ 0.6	22.3	-	-	-	-	RNAV 1
090	TF	UPKUP	-	048°(047.8°)	+ 0.6	14.5	-	-	-	-	RNAV 1

CHANGE : CHART TITLE. REVISED TABULAR DESCRIPTION.