

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**

**LAMPANG / Lampang (VTCL)
RNAV RWY36**

IBIRI1A IGNAX1A
OMDIL1A VENAG1A

TABULAR DESCRIPTION

RNP RWY36											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
IBIRI1A FROM Y33											
010	IF	IBIRI	-	-	+1.1	-	-	+7000	-	-	RNP1
020	TF	BOVBA	-	023° (021.8°)	+1.1	9.8	-	+5000	230	-	RNP1
030	TF	CL305	-	038° (036.8°)	+1.1	3.0	-	+4000	230	-	RNP1
040	TF	SATBO	-	038° (036.8°)	+1.1	3.2	-	+3300	210	-	RNP1
IGNAX1A FROM W9											
010	IF	IGNAX	-	-	+1.1	-	-	+7000	-	-	RNP1
020	TF	MADBU	-	329° (327.7°)	+1.1	7.6	-	+6000	230	-	RNP1
030	TF	BOVBA	-	329° (327.7°)	+1.1	4.1	-	+5000	230	-	RNP1
040	TF	CL305	-	038° (036.8°)	+1.1	3.0	-	+4000	230	-	RNP1
050	TF	SATBO	-	038° (036.8°)	+1.1	3.2	-	+3300	210	-	RNP1
OMDIL1A FROM W13											
010	IF	OMDIL	-	-	+1.1	-	-	+7000	-	-	RNP1
020	TF	TENEX	-	284° (282.7°)	+1.1	6.0	-	+6000	-	-	RNP1
030	TF	IGNUM	-	222° (220.6°)	+1.1	15.9	-	+6000	230	-	RNP1
040	TF	CL301	-	312° (310.5°)	+1.1	5.0	-	+5000	230	-	RNP1
050	TF	SATBO	-	312° (310.5°)	+1.1	4.6	-	+3300	210	-	RNP1
VENAG1A FROM W23											
010	IF	VENAG	-	-	+1.1	-	-	+7000	-	-	RNP1
020	TF	IGNUM	-	334° (333.3°)	+1.1	6.8	-	+6000	230	-	RNP1
030	TF	CL301	-	312° (310.5°)	+1.1	5.0	-	+5000	230	-	RNP1
040	TF	SATBO	-	312° (310.5°)	+1.1	4.6	-	+3300	210	-	RNP1