

**STANDARD DEPARTURE CHART -  
INSTRUMENT (SID) - ICAO**

**BANGKOK/Suvarnabhumi Intl (VTBS)  
RNAV RWY02L**

ALBOS1F BONVO1F BUT1F DOSBU1F  
GOMES1F HHN1F KASNI1F LIPLI1F  
NOBER2F NUNLI1F OLVUK1F PASTO1F  
REGOS1F RIVDU1F RYN1F SELKA1F  
SEMBO2F TARED1F UKERA1F VANKO1F

**TABULAR DESCRIPTION (8)**

RNAV RWY02L											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/TCH	Navigation Specification
TARED1F TO G463/P646											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	BS131	-	015°(014.4°)	+ 0.6	6.7	-	-	-	-	RNAV 1
060	TF	BS132	-	314°(313.4°)	+ 0.6	9.4	-	-10000; +8000	-	-	RNAV 1
070	TF	BS133	-	280°(278.9°)	+ 0.6	10.0	-	+11000	-	-	RNAV 1
080	TF	BS134	-	280°(278.9°)	+ 0.6	10.6	-	+FL140	-	-	RNAV 1
090	TF	TEMPO	-	279°(278.8°)	+ 0.6	25.1	-	-	-	-	RNAV 1
100	TF	TARED	-	304°(303.6°)	+ 0.6	27.6	-	-	-	-	RNAV 1
UKERA1F TO G458, W31											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	BS131	-	015°(014.4°)	+ 0.6	6.7	-	-	-	-	RNAV 1
060	TF	BS132	-	314°(313.4°)	+ 0.6	9.4	-	-10000; +8000	-	-	RNAV 1
070	TF	BS133	-	280°(278.9°)	+ 0.6	10.0	-	+11000	-	-	RNAV 1
080	TF	BS134	-	280°(278.9°)	+ 0.6	10.6	-	+FL140	-	-	RNAV 1
090	TF	POTEP	-	212°(211.5°)	+ 0.6	29.5	-	+FL200	-	-	RNAV 1
100	TF	TUPKA	-	164°(163.0°)	+ 0.6	22.4	-	-	-	-	RNAV 1
110	TF	SABIS	-	181°(180.5°)	+ 0.6	20.3	-	-	-	-	RNAV 1
120	TF	UKERA	-	191°(189.9°)	+ 0.6	58.5	-	-	-	-	RNAV 1