

TABULAR DESCRIPTION (2)

RNAV RWY36											
Serial	Path	Waypoint Identifier	Flyover	Course	Magnetic	Distance	Turn	Altitude	Speed	VPA/	Navigation
Number	Descriptor			°M (°T)	Variation	(NM)	Direction	(FT)	(KT)	TCH	Specification
PANTA2C TO W9, Y7											
010	-	DER RWY36	-	-	+0.6	-	-	-	-	-	RNAV 1
020	CF	CC202	-	001° (000.1°)	+0.6	11.3	-	+4500	-	-	RNAV 1
030	TF	CC203	-	091° (090.1°)	+0.6	7.0	-	-	-	-	RNAV 1
040	TF	POVUT	-	181° (180.2°)	+0.6	14.0	-	-11000	-250	-	RNAV 1
050	TF	CC205	-	181° (180.2°)	+0.6	4.0	-	-	-260	-	RNAV 1
060	TF	CC206	-	181° (180.2°)	+0.6	6.9	-	+FL 130	-	-	RNAV 1
070	TF	NUDMA	-	181° (180.2°)	+0.6	2.8	-	+FL 140	-	-	RNAV 1
080	TF	PANTA	-	141° (140.5°)	+0.6	21.2	-	-	-	-	RNAV 1
PUMAM2C TO A581/W7											
010	-	DER RWY36	-	-	+0.6	-	-	-	-	-	RNAV 1
020	CF	CC202	-	001° (000.1°)	+0.6	11.3	-	+4500	-	-	RNAV 1
030	TF	CC203	-	091° (090.1°)	+0.6	7.0	-	-	-	-	RNAV 1
040	TF	POVUT	-	181° (180.2°)	+0.6	14.0	-	-11000	-250	-	RNAV 1
050	TF	CC205	-	181° (180.2°)	+0.6	4.0	-	-	-260	-	RNAV 1
060	TF	CC206	-	181° (180.2°)	+0.6	6.9	-	+FL 130	-	-	RNAV 1
070	TF	NUDMA	-	181° (180.2°)	+0.6	2.8	-	+FL 140	-	-	RNAV 1
080	TF	CC211	-	214° (213.5°)	+0.6	16.0	-	-	-	-	RNAV 1
090	TF	PUMAM	-	214° (213.4°)	+0.6	10.0	-	-	-	-	RNAV 1
IGUDA2C TO Y36											
010	-	DER RWY36	-	-	+0.6	-	-	-	-	-	RNAV 1
020	CF	CC202	-	001° (000.1°)	+0.6	11.3	-	+4500	-	-	RNAV 1
030	TF	CC203	-	091° (090.1°)	+0.6		-	-	-	-	RNAV 1
040	TF	POVUT	-	181° (180.2°)	+0.6	14.0	-	-11000	-250	-	RNAV 1
050	TF	CC205	-	181° (180.2°)	+0.6	4.0	-	-	-260	-	RNAV 1
060	TF	CC207	-	091° (090.2°)	+0.6	8.9	-	+FL 130	-260	-	RNAV 1
070	TF	CC215	-	073° (072.3°)	+0.6	7.2	-	+FL 140	-260	-	RNAV 1
080	TF	IGUDA	-	012° (011.1°)	+0.6	8.7	-	-FL150	-260	-	RNAV 1

CHANGE: REVISED TABULAR DESCRIPTION.