

TABULAR DESCRIPTION (2)

RNAV RWY21L/21R											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
NAKON3A											
TRANSITION SEMBO FROM A464											
010	IF	SEMBO	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	TF	NAKON	-	129°(128.3°)	+ 0.6	18.9	-	-FL130	-250	-	RNAV 1
TRANSITION TL FROM W9/Y28, Y7											
010	IF	TL	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	TF	NAKON	-	160°(159.5°)	+ 0.6	36.5	-	-FL130	-250	-	RNAV 1
TRANSITION NOBER FROM B346/W39, W21											
010	IF	NOBER	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	TF	NAKON	-	195°(194.4°)	+ 0.6	35.3	-	-FL130	-250	-	RNAV 1
TRANSITION ALBOS FROM R474											
010	IF	ALBOS	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	TF	NAKON	-	266°(265.3°)	+ 0.6	29.8	-	-FL130	-250	-	RNAV 1
010	IF	NAKON	-	-	+ 0.6	-	-	-FL130	-250	-	RNAV 1
020	TF	DOGVA	-	165°(164.4°)	+ 0.6	11.8	-	-9000	-	-	RNAV 1
030	TF	BD114	-	165°(164.5°)	+ 0.6	6.9	-	-	-220	-	RNAV 1
040	TF	AROKA	-	165°(164.5°)	+ 0.6	13.2	-	-5000	-	-	RNAV 1
050	TF	BD111	-	165°(164.5°)	+ 0.6	7.0	-	+2600	-190	-	RNAV 1

CHANGE: CANCEL DOGVA SPEED RESTRICTION. BD114 SPEED RESTRICTION ADDED.