

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**BANGKOK/Suvarnabhumi Intl (VTBS)
RNAV RWY02L**

ALBOS1F BONVO1F BUT1F DOSBU1F
GOMES1F HHN1F KASNI1F LIPLI1F
NOBER2F NUNLI1F OLVUK1F PASTO1F
REGOS1F RYN1F SELKA1F SEMBO2F
TARED1F UKERA1F UGUVO1F VANKO1F

TABULAR DESCRIPTION (7)

RNAV RWY02L											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/TCH	Navigation Specification
SELKA1F TO A1, Y14											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	ASANI	-	091°(090.4°)	+ 0.6	11.3	-	-8000	-	-	RNAV 1
060	TF	SELKA	-	062°(061.1°)	+ 0.6	60.7	-	-	-	-	RNAV 1
SEMBO2F TO A464											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	BS131	-	015°(014.4°)	+ 0.6	6.7	-	-	-	-	RNAV 1
060	TF	BS135	-	015°(014.4°)	+ 0.6	5.3	-	-	-	-	RNAV 1
070	TF	BS136	-	015°(014.5°)	+ 0.6	16.5	-	-	-	-	RNAV 1
080	TF	BS137	-	285°(284.6°)	+ 0.6	15.2	-	-FL150; +FL140	-	-	RNAV 1
090	TF	BS138	-	285°(284.5°)	+ 0.6	13.3	-	-	-	-	RNAV 1
100	TF	RVDU	-	343°(342.1°)	+ 0.6	17.4	-	-	-	-	RNAV 1
110	TF	SEMBO	-	340°(338.9°)	+ 0.6	12.2	-	-	-	-	RNAV 1
TARED1F TO G463/P646											
010	-	DER RWY02L	-	-	+ 0.6	-	-	-	-	-	RNAV 1
020	VA	-	-	018°(017.7°)	+ 0.6	-	-	+700	-	-	RNAV 1
030	DF	BS129	-	-	+ 0.6	-	L	-	-	-	RNAV 1
040	TF	BS130	-	015°(014.4°)	+ 0.6	5.6	-	-	-	-	RNAV 1
050	TF	BS131	-	015°(014.4°)	+ 0.6	6.7	-	-	-	-	RNAV 1
060	TF	BS132	-	314°(313.4°)	+ 0.6	9.4	-	-10000; +8000	-	-	RNAV 1
070	TF	BS133	-	280°(278.9°)	+ 0.6	10.0	-	+11000	-	-	RNAV 1
080	TF	BS134	-	280°(278.9°)	+ 0.6	10.6	-	+FL140	-	-	RNAV 1
090	TF	TEMPO	-	279°(278.8°)	+ 0.6	25.1	-	-	-	-	RNAV 1
100	TF	TARED	-	304°(303.6°)	+ 0.6	27.6	-	-	-	-	RNAV 1