

**STANDARD DEPARTURE CHART -
INSTRUMENT (SID) - ICAO**

**PHUKET/Phuket Intl (VTSP)
RNAV RWY27**

ANPUB1B EMRIT1B EPGOT1B IGEV1B ONET1B REBED1B
SATVA1B SAVSA1B SUSID1B UBEN1B UPSAB1B

TABULAR DESCRIPTION (1)

RNAV RWY27

Serial	Path	Waypoint Identifier	Flyover	Course	Magnetic	Distance	Turn	Altitude	Speed	VPA/	Navigation
Number	Descriptor			° M (° T)	Variation	(NM)	Direction	(FT)	(KT)	TCH	Specification
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	L	+2500	-270	-	RNAV1
030	DF	SP401	-	-	+0.4	-	L	-	-	-	RNAV1
040	TF	SP404	-	113°(112.4°)	+0.4	16.7	-	+11000	-	-	RNAV1
050	TF	REBED	-	113°(112.4°)	+0.4	8.1	-	-	-	-	RNAV1
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	L	+2500	-270	-	RNAV1
030	DF	SP401	-	-	+0.4	-	L	-	-	-	RNAV1
040	TF	SP402	-	088°(087.8°)	+0.4	16.7	-	+11000	-	-	RNAV1
050	TF	EPGOT	-	088°(087.9°)	+0.4	14.5	-	-	-	-	RNAV1
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	L	+2500	-270	-	RNAV1
030	DF	SP401	-	-	+0.4	-	L	-	-	-	RNAV1
040	TF	SP402	-	088°(087.8°)	+0.4	16.7	L	+11000	-	-	RNAV1
050	TF	EMRIT	-	054°(053.9°)	+0.4	21.3	-	-	-	-	RNAV1
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	-	+2500	-270	-	RNAV1
030	DF	SP501	-	-	+0.4	-	R	-	-	-	RNAV1
040	TF	UBNEN	-	268°(267.9°)	+0.4	18.1	-	-	-	-	RNAV1
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	-	+2500	-270	-	RNAV1
030	DF	SP501	-	-	+0.4	-	L	-	-	-	RNAV1
040	TF	ANPUB	-	225°(224.5°)	+0.4	20.0	-	-	-	-	RNAV1
010	-	DER RWY27	-	-	+0.4	-	-	-	-	-	RNAV1
020	CA	-	-	265°(264.6°)	+0.4	-	R	+2500	-270	-	RNAV1
030	DF	SP601	-	-	+0.4	-	L	-	-	-	RNAV1
040	TF	SATVA	-	306°(305.1°)	+0.4	17.0	-	-	-	-	RNAV1

CHANGE: MAG VAR.