

**STANDARD ARRIVAL CHART -
INSTRUMENT (STAR) - ICAO**

**PHUKET/Phuket Intl (VTSP)
RNAV RWY09**

ANPUB1C EMRIT1C EPGOT1C IGEV1C MONBU1C ONET1C
SATVA1C SAVSA1C SUSID1C UBHEN1C UPSAB1C URGAD1C

TABULAR DESCRIPTION (1)

RNAV RWY09

Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/TCH	Navigation Specification
010	IF	ONET1	-	-	+0.4	-	-	+FL130	-	-	RNAV1
020	TF	SP703	-	262°(261.8°)	+0.4	16.6	-	+FL130	-	-	RNAV1
030	TF	MILAN	-	262°(261.4°)	+0.4	24.5	-	-	-	-	RNAV1
040	TF	SP702	-	262°(261.3°)	+0.4	5.0	L	+4000	-230	-	RNAV1
050	TF	KALIM	-	175°(174.6°)	+0.4	6.0	L	+4000	-200	-	RNAV1
010	IF	MONBU	-	-	+0.4	-	-	-10000	-	-	RNAV1
020	TF	MILAN	-	247°(246.8°)	+0.4	38.2	R	-	-	-	RNAV1
030	TF	SP702	-	262°(261.3°)	+0.4	5.0	L	+4000	-230	-	RNAV1
040	TF	KALIM	-	175°(174.6°)	+0.4	6.0	L	+4000	-200	-	RNAV1
010	IF	SAVSA	-	-	+0.4	-	-	-10000	-	-	RNAV1
020	TF	MILAN	-	240°(240.0°)	+0.4	36.6	R	-	-	-	RNAV1
030	TF	SP702	-	262°(261.3°)	+0.4	5.0	L	+4000	-230	-	RNAV1
040	TF	KALIM	-	175°(174.6°)	+0.4	6.0	L	+4000	-200	-	RNAV1
010	IF	IGEV1	-	-	+0.4	-	-	-10000	-	-	RNAV1
020	TF	TARPU	-	233°(232.3°)	+0.4	29.5	L	-7000	-230	-	RNAV1
030	TF	SP702	-	175°(174.1°)	+0.4	7.4	-	+4000	-230	-	RNAV1
040	TF	KALIM	-	175°(174.6°)	+0.4	6.0	L	+4000	-200	-	RNAV1
010	IF	SUSID	-	-	+0.4	-	-	-10000	-	-	RNAV1
020	TF	TARPU	-	225°(224.7°)	+0.4	25.9	L	-7000	-230	-	RNAV1
030	TF	SP702	-	175°(174.1°)	+0.4	7.4	-	+4000	-230	-	RNAV1
040	TF	KALIM	-	175°(174.6°)	+0.4	6.0	L	+4000	-200	-	RNAV1