

**STANDARD ARRIVAL CHART -  
INSTRUMENT (STAR) - ICAO**

TRANSITION ALTITUDE  
11000 FT

**SONGKHLA / Hat Yai Intl (VTSS)  
RNAV RWY26**

ELREM1A ENVON1A  
KENNE1A OBLEX1A PADPA1A  
PIMER1A TAMOS1A TAXEB1A

**TABULAR DESCRIPTION (1)**

RNAV RWY26											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
ELREM1A FROM W17											
010	IF	ELREM	-	-	+0.3	-	-	+10000	-	-	RNP 1
020	TF	SS211	-	132° (132.1°)	+0.3	8.8	-	+10000	-	-	RNP 1
030	TF	KIBAB	-	132° (132.1°)	+0.3	7.0	-	+10000	-	-	RNP 1
040	TF	SS218	-	094° (093.6°)	+0.3	6.2	-	+10000	-	-	RNP 1
050	TF	LETMO	-	094° (093.6°)	+0.3	9.6	-	+8000	-	-	RNP 1
060	TF	KASLA	-	175° (175.1°)	+0.3	10.2	-	+5000	-230	-	RNP 1
070	TF	RISRO	-	175° (175.1°)	+0.3	7.0	-	+3000	-230	-	RNP 1
ENVON1A FROM W28											
010	IF	ENVON	-	-	+0.3	-	-	+10000	-	-	RNP 1
020	TF	SS212	-	165° (164.7°)	+0.3	7.4	-	+10000	-	-	RNP 1
030	TF	KIBAB	-	165° (164.7°)	+0.3	7.0	-	+10000	-	-	RNP 1
040	TF	SS218	-	094° (093.6°)	+0.3	6.2	-	+10000	-	-	RNP 1
050	TF	LETMO	-	094° (093.6°)	+0.3	9.6	-	+8000	-	-	RNP 1
060	TF	KASLA	-	175° (175.1°)	+0.3	10.2	-	+5000	-230	-	RNP 1
070	TF	RISRO	-	175° (175.1°)	+0.3	7.0	-	+3000	-230	-	RNP 1
KENNE1A FROM Y18											
010	IF	KENNE	-	-	+0.3	-	-	-7000	-	-	RNP 1
020	TF	PIMUV	-	360° (359.9°)	+0.3	8.9	-	+5000	-230	-	RNP 1
030	TF	RISRO	-	308° (307.9°)	+0.3	7.9	-	+3000	-230	-	RNP 1
OBLEX1A FROM M757											
010	IF	OBLEX	-	-	+0.3	-	-	+10000	-	-	RNP 1
020	TF	LETMO	-	175° (175.1°)	+0.3	15.2	-	+8000	-	-	RNP 1
030	TF	KASLA	-	175° (175.1°)	+0.3	10.2	-	+5000	-230	-	RNP 1
040	TF	RISRO	-	175° (175.1°)	+0.3	7.0	-	+3000	-230	-	RNP 1
PADPA1A FROM W14											
010	IF	PADPA	-	-	+0.3	-	-	+10000	-	-	RNP 1
020	TF	ISDM	-	094° (093.6°)	+0.3	12.7	-	+10000	-	-	RNP 1
030	TF	KIBAB	-	094° (093.6°)	+0.3	9.6	-	+10000	-	-	RNP 1
040	TF	SS218	-	094° (093.6°)	+0.3	6.2	-	+10000	-	-	RNP 1
050	TF	LETMO	-	094° (093.6°)	+0.3	9.6	-	+8000	-	-	RNP 1
060	TF	KASLA	-	175° (175.1°)	+0.3	10.2	-	+5000	-230	-	RNP 1
070	TF	RISRO	-	175° (175.1°)	+0.3	7.0	-	+3000	-230	-	RNP 1

CHANGE : MAG VAR.