

INSTRUMENT **AERODROME ELEV 90 FT**
APPROACH **HEIGHTS RELATED TO**
CHART - ICAO **THR RWY26 - ELEV 58 FT**

SONGKHLA / Hat Yai Intl (VTSS)

ILS or LOC z RWY26

TABULAR DESCRIPTION

ILS or LOC z RWY26											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/TCH	Navigation Specification
010	IF	(IAF) PIMUV	-	-	+0.3	-	-	+5000	-230	-	RNP 1
020	TF	(IF) RISRO	-	308°(307.9°)	+0.3	7.9	-	+3000	-230	-	RNP 1
010	IF	(IAF) KASLA	-	-	+0.3	-	-	+5000	-230	-	RNP 1
020	TF	(IF) RISRO	-	175°(175.1°)	+0.3	7.0	-	+3000	-230	-	RNP 1
010	IF	(IF) RISRO	-	-	+0.3	-	-	+3000	-230	-	RNP 1
TRANSITION TO ILS or LOC											
020	TF	SS203	-	263°(262.9°)	+0.3	3.2	-	@2400	-	-	ILS
030	TF	(FAP/FAF) SS202	-	263°(262.9°)	+0.3	3.2	-	@1500	-	-	ILS
040	TF	(MAPt@THR26) SS201	Y	263°(262.9°)	+0.3	4.4	-	@108	-	-3.0/50	ILS
050	CA	-	-	263°(262.9°)	+0.3	-	-	+1000	-200	-	RNP 1
060	DF	SS205	-	-	+0.3	-	L	+2300	-200	-	RNP 1
070	TF	SS204	-	083°(082.8°)	+0.3	14.8	-	+3000	-200	-	RNP 1
080	TF	(IF) RISRO	-	353°(352.9°)	+0.3	7.0	-	+3000	-230	-	RNP 1
090	HM	(IF) RISRO	Y	263°(262.9°)	+0.3	1 minute	R	+3000	-230	-	RNP 1

WAYPOINT LIST

ILS or LOC z RWY26		
Waypoint Identifier	Coordinates	
KASLA	07° 04' 25.58" N	100° 34' 39.39" E
PIMUV	06° 52' 33.56" N	100° 41' 31.05" E
RISRO	06° 57' 25.07" N	100° 35' 15.76" E
SS201	06° 56' 03.89" N	100° 24' 28.52" E
SS202	06° 56' 36.96" N	100° 28' 51.91" E
SS203	06° 57' 01.07" N	100° 32' 04.19" E
SS204	06° 50' 26.30" N	100° 36' 08.25" E
SS205	06° 48' 34.95" N	100° 21' 20.76" E

CHANGE : MAG VAR.