

TABULAR DESCRIPTION

ILS or LOC z RWY02											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ RDH	Navigation Specification
010	IF	(IAF) SAKUB	-	-	+0.5	-	-	+9000	-	-	RNP 1
020	TF	SR024	-	204° (203.1°)	+0.5	11.0	-	+9000	-	-	RNP 1
030	TF	SR023	-	204° (203.1°)	+0.5	11.0	-	-7000	-	-	RNP 1
040	TF	BIGDA	-	204° (203.7°)	+0.5	15.0	-	+6000	-	-	RNP 1
050	TF	(IF) OLBUN	-	294° (293.7°)	+0.5	7.0	-	+3500	-200	-	RNP 1
010	IF	(IAF) TOGIM	-	-	+0.5	-	-	-7000	-	-	RNP 1
020	TF	BIGDA	-	288° (287.7°)	+0.5	16.0	-	+6000	-	-	RNP 1
030	TF	(IF) OLBUN	-	294° (293.7°)	+0.5	7.0	-	+3500	-200	-	RNP 1
010	IF	(IAF) ELPUT	-	-	+0.5	-	-	-7000	-	-	RNP 1
020	TF	SR001	-	356° (355.4°)	+0.5	5.0	-	+5500	-	-	RNP 1
030	TF	(IF) OLBUN	-	356° (355.4°)	+0.5	7.8	-	+3500	-200	-	RNP 1
010	IF	(IAF) SUDEX	-	-	+0.5	-	-	@5000	-	-	RNP 1
020	TF	SR025	-	127° (126.7°)	+0.5	5.5	-	-5000	-	-	RNP 1
030	TF	(IF) OLBUN	-	114° (113.7°)	+0.5	7.0	-	+3500	-200	-	RNP 1
010	IF	(IF) OLBUN	-	-	+0.5	-	-	+3500	-200	-	RNP 1
TRANSITION TO ILS or LOC											
020	TF	(FAF/FAP) SR022	-	024° (023.7°)	+0.5	5.4	-	@2300	-	-	ILS
030	TF	(MAPt) SR021	Y	024° (023.7°)	+0.5	4.8	-	@1000	-	-3.0/50	ILS
040	CF	SR002	-	013° (012.8°)	+0.5	7.7	-	+2000	-170	-	RNP 1
050	DF	SUDEX	-	-	+0.5	-	L	@5000	-	-	RNP 1
060	HM	SUDEX	Y	127° (126.7°)	+0.5	1 minute	R	@5000	-230	-	RNP 1