

TABULAR DESCRIPTION

RNP RWY18											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course °M (°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
010	IF	(IAF) UBCOX	-	-	+0.9	-	-	+6000	-230	-	RNP APCH
020	TF	CL102	-	135° (134.3°)	+0.9	5.0	-	+4700	-210	-	RNP APCH
030	TF	(IF) ATKIM	-	135° (134.3°)	+0.9	3.9	-	+3500	-200	-	RNP APCH
010	TF	(IAF) UNTIM	-	-	+0.9	-	-	+5000	-230	-	RNP APCH
020	TF	(IF) ATKIM	-	266° (265.4°)	+0.9	8.0	-	+3500	-200	-	RNP APCH
010	IF	(IF) ATKIM	-	-	+0.9	-	-	+3500	-200	-	RNP APCH
020	TF	CL112	-	176° (175.4°)	+0.9	3.0	-	+2900	-	-	RNP APCH
020	TF	(FAF) CL122	-	176° (175.4°)	+0.9	3.0	-	@2100	-	-	RNP APCH
030	TF	(MAPt @ THR18) CL132	Y	176° (175.4°)	+0.9	4.0	-	@842	-	-3.0/50	RNP APCH
040	TF	CL142	-	176° (175.4°)	+0.9	8.9	-	+2300	-200	-	RNP APCH
050	TF	CL152	-	086° (085.4°)	+0.9	5.0	-	+3000	-200	-	RNP APCH
060	TF	CL162	-	005° (004.5°)	+0.9	8.0	-	+4100	-	-	RNP APCH
070	TF	UNTIM	-	005° (004.5°)	+0.9	11.1	-	+5000	-230	-	RNP APCH
080	HM	UNTIM	Y	266° (265.4°)	+0.9	1 minute	R	+5000	-230	-	RNP APCH

CHANGE: MAG VAR. COURSE ATKIM TO CL112, CL112 TO CL122, CL122 TO CL132, CL132 TO CL142, CL142 TO CL152, CL152 TO CL162, CL162 TO UNTIM, UNTIM TO ATKIM.