

TABULAR DESCRIPTION (7)

| RNAV RWY01           |                 |                     |         |                  |                    |               |                |                   |            |          |                          |
|----------------------|-----------------|---------------------|---------|------------------|--------------------|---------------|----------------|-------------------|------------|----------|--------------------------|
| Serial Number        | Path Descriptor | Waypoint Identifier | Flyover | Course ° M (° T) | Magnetic Variation | Distance (NM) | Turn Direction | Altitude (FT)     | Speed (KT) | VPA/ TCH | Navigation Specification |
| SEMBO3K TO A464      |                 |                     |         |                  |                    |               |                |                   |            |          |                          |
| 010                  | -               | DER RWY01           | -       | -                | + 0.7              | -             | -              | -                 | -          | -        | RNAV 1                   |
| 020                  | VA              | -                   | -       | 015°(014.4°)     | + 0.7              | -             | -              | +700              | -          | -        | RNAV 1                   |
| 030                  | DF              | BS120               | -       | -                | + 0.7              | -             | R              | -                 | -          | -        | RNAV 1                   |
| 040                  | TF              | ASANI               | -       | 054°(053.0°)     | + 0.7              | 8.9           | -              | -6000             | -          | -        | RNAV 1                   |
| 050                  | TF              | BS127               | -       | 004°(003.3°)     | + 0.7              | 5.8           | -              | -8000             | -          | -        | RNAV 1                   |
| 060                  | TF              | BS128               | -       | 004°(003.3°)     | + 0.7              | 20.5          | -              | -                 | -          | -        | RNAV 1                   |
| 070                  | TF              | BS137               | -       | 285°(284.6°)     | + 0.7              | 21.1          | -              | -FL150;<br>+FL140 | -          | -        | RNAV 1                   |
| 080                  | TF              | BS138               | -       | 285°(284.5°)     | + 0.7              | 13.3          | -              | -                 | -          | -        | RNAV 1                   |
| 090                  | TF              | RIVDU               | -       | 343°(342.1°)     | + 0.7              | 17.4          | -              | -                 | -          | -        | RNAV 1                   |
| 100                  | TF              | SEMBO               | -       | 340°(338.9°)     | + 0.7              | 12.2          | -              | -                 | -          | -        | RNAV 1                   |
| TARED3K TO G463/P646 |                 |                     |         |                  |                    |               |                |                   |            |          |                          |
| 010                  | -               | DER RWY01           | -       | -                | + 0.7              | -             | -              | -                 | -          | -        | RNAV 1                   |
| 020                  | VA              | -                   | -       | 015°(014.4°)     | + 0.7              | -             | -              | +700              | -          | -        | RNAV 1                   |
| 030                  | DF              | BS120               | -       | -                | + 0.7              | -             | R              | -                 | -          | -        | RNAV 1                   |
| 040                  | TF              | ASANI               | -       | 054°(053.0°)     | + 0.7              | 8.9           | -              | -6000             | -          | -        | RNAV 1                   |
| 050                  | TF              | BS127               | -       | 004°(003.3°)     | + 0.7              | 5.8           | -              | -8000             | -          | -        | RNAV 1                   |
| 060                  | TF              | BS135               | -       | 305°(304.6°)     | + 0.7              | 10.4          | -              | -                 | -          | -        | RNAV 1                   |
| 070                  | TF              | BS132               | -       | 280°(278.9°)     | + 0.7              | 8.2           | -              | -10000;<br>+8000  | -          | -        | RNAV 1                   |
| 080                  | TF              | BS133               | -       | 280°(278.9°)     | + 0.7              | 10.0          | -              | +11000            | -          | -        | RNAV 1                   |
| 090                  | TF              | BS134               | -       | 280°(278.9°)     | + 0.7              | 10.6          | -              | +FL140            | -          | -        | RNAV 1                   |
| 100                  | TF              | TEMPO               | -       | 280°(278.8°)     | + 0.7              | 25.1          | -              | -                 | -          | -        | RNAV 1                   |
| 110                  | TF              | TARED               | -       | 304°(303.6°)     | + 0.7              | 27.6          | -              | -                 | -          | -        | RNAV 1                   |