

TABULAR DESCRIPTION

RNP RWY20L											
Serial Number	Path Descriptor	Waypoint Identifier	Flyover	Course ° M (° T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT)	VPA/ TCH	Navigation Specification
010	IF	(IAF) REGIR	-	-	+0.7	-	-	+5000	-220	-	RNP APCH
020	TF	(IF) RUMAD	-	195°(194.4°)	+0.7	5.0	-	+4000	-	-	RNP APCH
030	TF	REVMO	-	195°(194.4°)	+0.7	3.7	-	+3000	-	-	RNP APCH
040	TF	(FAF) BS780	-	195°(194.4°)	+0.7	6.0	-	@1600	-	-	RNP APCH
050	TF	(MAPt @ THR20L) BS781	Y	195°(194.4°)	+0.7	4.9	-	@54	-	-3.0/50	RNP APCH
060	CF	DE20L	Y	195°(194.4°)	+0.7	2.0	-	-	-	-	RNP APCH
070	DF	BS601	-	-	+0.7	-	R	-	-	-	RNP APCH
080	TF	BS602	-	181°(180.4°)	+0.7	3.0	-	-3000	-210	-	RNP APCH
090	TF	BS603	-	105°(104.3°)	+0.7	17.4	-	-3000	-	-	RNP APCH
100	TF	BS605	-	015°(014.6°)	+0.7	18.0	-	+5000	-	-	RNP APCH
110	TF	OBDIP	-	015°(014.6°)	+0.7	10.1	-	+5000	-	-	RNP APCH
120	HM	OBDIP	Y	015°(014.6°)	+0.7	1 minute	R	+5000	-230	-	RNP APCH

WAYPOINT LIST

RNP RWY20L		
Waypoint Identifier	Coordinates	
REGIR	14° 01' 17.67" N	100° 49' 36.72" E
RUMAD	13° 56' 25.87" N	100° 48' 19.81" E
REVMO	13° 52' 48.77" N	100° 47' 22.64" E
BS780	13° 46' 59.12" N	100° 45' 50.66" E
BS781	13° 42' 13.21" N	100° 44' 35.44" E
DE20L	13° 40' 16.60" N	100° 44' 04.79" E
BS601	13° 33' 07.17" N	100° 36' 56.80" E
BS602	13° 30' 06.39" N	100° 36' 55.58" E
BS603	13° 25' 46.90" N	100° 54' 12.14" E
BS605	13° 43' 15.45" N	100° 58' 51.48" E
OBDIP	13° 53' 03.74" N	101° 01' 28.52" E